



Jute Matting

DESCRIPTION:

Jute Matting is an organic geotextile which aids in weed and erosion control. An environmentally friendly way of protecting young trees and shrubs by reducing competing weeds and the need to use damaging herbicide. Because the Jute Matting allows both air and water to pass unimpeded through its construction, the soil beneath it can breathe, promoting growth of desired plants while reducing evaporation and minimising watering needs. Jute Matting is the simplest, safest, and most cost effective method of promoting new growth on the worst affected slopes because it enhances water filtration whilst protecting precious topsoils.



APPLICATIONS:

- Slopes
- Garden beds
- Landscaping or roadsides
- Revegetating gardens
- Coastal areas with high winds
- Wetlands and riparian slopes
- Can be fastened with a "U" shaped pin



FASTENING PINS SOLD SEPARATELY



All Stake Supply Jute Matting



FEATURES / BENEFITS:

Weed Control:

The thick natural material stops sunlight from promoting weed growth.

Water retention:

The matting increases water retention which aids the establishment of long term vegetation. It also reduces watering costs.

Erosion Control:

Installing jute matting will suppress weed growth, retain moisture and protect the top soil from eroding.

A breathable natural material which promotes growth of desired plants.

Fine Jute Matting has no scrim and is used as a lighter alternative.

Heavy Jute Matting is used for sand dunes and requires 300mm pins.

INSTALLATION:

On sloping ground, dig a trench and bury the matting at the top of the slope 150 - 200mm. Roll out the matting and pin it approx 3 pins per m². For multiple rolls, the matting needs to be overlaid by 100-200mm.

The matting is pinned with a U shaped fastening pin, by hand or you can use a Tackler gun which is a fast and easy way of installing numerous rolls.

Tips

For easier installation on large planting jobs, purchase slitted jute rolls which have 5 slits per m².

The matting is a 100% biodegradable organic product which will break down over time.

SPECIFICATIONS:

Fine	2m x 50m	280gsm
Medium	1.83m x 25m	750-800gsm
Medium Slitted	1.83m x 25m	750-800gsm (5 slits per m ²)
Heavy	1.83m x 25m	1300 gsm
Mats	370mm x 370mm	750-800gsm
Mats	600mm x 600mm	750-800gsm

Call us today on 1300 130 123

Visit www.allstake.com.au for our complete range of products